



# kopex - ventilflex M10

## KX.T.8131 ● 8310

	<p><b>Description:</b> Strip-wrapped, multilayer flexible hose; round section; corrugated profile</p>
<b>Characteristics:</b>	Lightweight with very small bend radius, easy to cut and fit Moderate resistance to heat and humidity
<b>Size range:</b>	From DN25 to DN80 Diameters not listed in the tab can be supplied on request for suitable quantities
<b>Supply condition:</b>	In rolls by the metre or in requested cut-lengths Standard supply at extended length; upon request in compact length
<b>Materials:</b>	Aluminium and Kraft paper
<b>Profile:</b>	 <p style="margin-left: 20px;"> <span style="color: brown;">—</span> Outer layer in Kraft paper  <span style="color: brown;">—</span> Middle layer in Aluminium  <span style="color: brown;">—</span> Inner layer in Kraft paper         </p>
<b>Construction:</b>	Strip-wrapping, pre-forming, and hot bonding
<b>Types:</b>	KX.T.8131.45.XXX Black outer layer in Kraft paper, middle layer in aluminium, inner layer in Kraft paper KX.T.8131.44.XXX Havana outer layer in Kraft paper, middle layer in aluminium, inner layer in Kraft paper. On request Extra-light dual-layer construction, inner aluminium, outer Kraft paper, Type KX.T.8310.XX.XXX
<b>Use:</b>	Suction and delivery of hot and cold air, non-abrasive powders, welding fumes, etc.
<b>Applications:</b>	Heating and ventilation ducts for automotive applications, caravans and campers, prefabricated houses, boats, etc. Connections between air filters. Exhaust fumes and powder ducts in workshops, etc.
<b>Temperature:</b>	Up to 120 °C

